

WorkForce Enterprise

WF-C20750 D4TW



With print speeds of up to 75ppm this eco-responsible MFP offers impressive reliability and high print yields, reducing operational costs

Print up to 100,000 pages in mono or 50,000 in colour without changing the supplies. This reliable, low maintenance 4-in-1 device² offers high-speed performance, superior image quality, all with significant sustainability advantages over laser models.

Superior quality at high speeds

The WorkForce Enterprise WF-C20750 delivers superior image quality at print speeds of up to 75ppm and a first copy out time (FCOT) of 5.4 seconds.

Super high ink yield

Print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies.¹ This means there is even less need for user intervention. Through fewer consumables and supplies, it also produces less waste. With low power consumption, the overall environmental impact of printing is cut dramatically.

Robust, high-end finishing capability

With advanced finishing such as booklet finisher and hole punch options, this device offers advanced finishing capability. It also offers a high paper capacity of up to 5,350 pages, increasing productivity further.


Heat-free technology

Epson Heat-Free Precision Core Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver an exceptional FCOT compared to laser technology.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson's new Epson Remote Services (ERS) which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

DATASHEET / BROCHURE



KEY FEATURES

- **Faster performance**
Fast FCOT of 5.4 seconds and print speeds of up to 75ppm
- **High capacity ink yield**
Users can print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies
- **Improved finishing capability**
Advanced finishing such as booklet finisher and hole punch options
- **Powerful scanning capability**
Thin paper support and improved scanning quality
- **Works with Epson Remote Services**
Cloud based, advanced diagnosis of Epson printers and MFPs

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ Micro TFP printhead
Nozzle Configuration	8,676 Nozzles Black, 8,676 Nozzles per Color
Minimum Droplet Size	3.5 pl
Ink Technology	DURABrite™ Pro
Category	Office Departmental
All-in-One Functions	Print, Scan, Copy

PRINT

First Page Out	Monochrome 5.4 Seconds, Colour 5.4 Seconds
Printing Speed ISO/IEC 24734	75 pages/min Monochrome, 75 pages/min Colour
Duplex Printing Speed ISO/IEC 24734	75 A4 Pages/min Monochrome, 75 A4 Pages/min Colour
Printing Speed ISO/IEC 24734 (A3)	45 pages/min Monochrome, 45 pages/min Colour
Maximum Printing Speed	75 pages/min Monochrome (plain paper 75 g/m ²), 75 pages/min Colour (plain paper 75 g/m ²)
Printing Resolution	600 x 2,400 DPI
Printing Volume	400,000 pages per month The maximum number of printed pages per month based on the performance capabilities of the printer, including ISO rated print speeds and paper handling capabilities.
Recommended Duty Cycle	8,000 - 100,000 pages per month
Colours	Black, Cyan, Yellow, Magenta

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

Double-sided scanning	Yes
Scanning Speed	60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 60 ipm (Colour, Single-sided, 300 dpi, ADF); 110 ipm (Monochrome, Double-sided, 300 dpi, ADF); 110 ipm (Colour, Double-sided, 300 dpi, Automatic Document Feeder);
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)
Advanced document integration	Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB Memory Device / Card
Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, PNG
Scanner type	Contact image sensor (CIS)
Optical Resolution	600 DPI x 600 DPI (Horizontal x Vertical)

WorkForce Enterprise WF-C20750 D4TW

WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide

PRODUCT SPECIFICATIONS

WorkForce Enterprise WF-C20750 D4TW

FAX

Type of fax	Walk-up black and white and colour fax capability
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page
Error correction mode	CCITU/ITU Group3 fax with Error Correction Mode
Fax speed dials (max)	2,000 names and numbers
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Fax to Folder, Address Book, Fax Preview, Polling Reception

COPY

Copy Speed	Up to 75 ipm Black, Up to 75 ipm Colour *Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)
Copy resolution (dpi)	600 x 1200
Reduction / Enlargement	25 % - 400 %
Maximum number of copies	9,999
Maximum Copy Size	A3

CONNECTIVITY

Network Printing Protocols	IPP, LDP, Port 9100, WSD
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping, SNMP 2.0c, SNMP 3.0
Network Protocol	IPv4, IPv6
Network Scanning Protocols	WSD-Scan, FTP
Interfaces	10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T), Gigabit ethernet interface, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi Direct, USB 1.1 Type A, USB 2.0 Type A, USB 3.0 Type B, Near Field Communication (NFC)
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)
Network Protocol	TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS

PAPER / MEDIA HANDLING

Paper Formats	A3, A4, Postcard, A3+, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Executive, Letter, Legal, HLT, No. 10 (Envelope), User defined, SRA3
Automatic Document Feed	150 pages
Compatible Paper Weight	60 g/m ² - 350 g/m ²
Duplex	Yes (A4/A3, plain paper)
Standard Paper input	2,350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray
Output Tray Capacity	550 Sheets
Maximum paper input	5,350
Number of paper trays	4

PAPER FEED RASF

Paper Input Name	RASF
Paper Formats	A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Letter, 20 x 25 cm, HLT, User defined, SRA3
Custom sizes	Min 55x 330 mm to Max 127x 1,200 mm
Compatible paper weight	60 g/m ² - 350 g/m ²
Paper Capacity 1	150 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED C1

Paper Input Name	C1
Paper Formats	A3, A4, A5, B4, B5, Letter, HLT, Executive
Custom sizes	Min 140x 297 mm to Max 182x 432 mm
Compatible paper weight	60 g/m ² - 160 g/m ²
Paper Capacity 1	550 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead

PRODUCT SPECIFICATIONS

WorkForce Enterprise WF-C20750 D4TW

{SPECGROUPNAMEPAPERFEEDC2-C4}

Paper Input Name	C2-C4
Paper Formats	A3, A4, A5, B4, B5, Letter, HLT
Custom sizes	Min 140x 297 mm to Max 182x 432 mm
Compatible paper weight	60 g/m ² - 160 g/m ²
Paper Capacity 1	550 80gsm
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED LCT

Paper Input Name	LCT
Paper Formats	A4, Letter
Compatible paper weight	60 g/m ² - 160 g/m ²
Paper Capacity 1	3,000 80gsm

PAPER FEED DUPLEX

Paper Input Name	Duplex
Compatible paper weight	60 g/m ² - 160 g/m ²

GENERAL

Energy Use	160 Watt (standalone copying, ISO/IEC 24712 pattern), 1.1 Watt (sleep mode), 76 Watt (Ready), 0.1 Watt (Power off), TEC 0.34 kWh/week
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	674 x 757 x 1,243 mm (Width x Depth x Height)
Product weight	177.1 kg
Compatible Operating Systems	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP Professional x64 Edition SP2
Sound Power	Operation: 7.5 B (A)
Noise	Operation: 60 dB (A)
Power supply	220V, 240V

ADDITIONAL FEATURES

Features	Touchscreen
Panel	Type: Color, Touchscreen, Diagonal: 22.7 cm
Media Handling	Duplex (A4/A3, plain paper)
Security Functions	Limit access function with Epson Web Config, Secure confidential printing with PIN code release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin Mode

OTHER FEATURES

Emulations	PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour
------------	--

SUPPLIES

- Maintenance box C13T671300

OPTIONAL ACCESSORIES

- 3000-sheet High Capacity Paper Tray C12C933041

LOGISTICS INFORMATION

SKU	C11CH87401 C11CH87401BY
EAN code	8715946677002

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com
Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04
(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742
Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00
Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621
Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min)
Switzerland 022 592 7923
Turkey (0212) 3360303 United Kingdom 0871 222 6702

1. *Approx. page yield with the WF-C20600. Actual yield will vary depending on images printed and usage conditions. For more information visit www.epson.eu/pageyield.
2. *Fax optional at an additional cost

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.